


# About ProspectSV





ProspectSV is a nonprofit cleantech innovation hub focused on advanced mobility and energy solutions for urban communities.

PROSPECT Silicon Valley

2



To accelerate the adoption of clean technologies in



## Advanced Mobility

Automated, connected, electric, and shared vehicles



Building Efficiency, Vehicle-to-Grid Integration, Distributed Energy Resources



✓ PROSPECT Silicon Valley

3

# **Energy Demonstration Programs**

Whole Foods ZNE



CalOp ACE




**REALIZE** 



PROSPECT Silicon Valley









# I Feel Bad For You!


1982 Average Energy Consumption per household 115 million BTUs x 80 million housing units = 9.2 trillion BTUs


VS


2009 Average Energy Consumption per household 90 million BTUs x 115 million housing units = 10.35 trillion BTUs


(eia.gov/todayinenergy/detail.php?id=6570)

# Number of Buildings


















# Retrofitting Existing Municipal Buildings to ZNE: The City of San Diego "ZN3" Project


Kristin Larson, AICP and LEED Green Associate October 10, 2019



## "San Diego ZN3"

Three City of San Diego public libraries are undergoing an integrated demand-side management demonstration to achieve ZNE through cost-effective energy efficiency upgrades, on-site renewable generation, enhanced building automation, pre- & post-installation monitoring, and occupant behavior analysis in order to provide a blueprint that shows ZNE is possible in existing municipal buildings.

Project Summary



# **ZNE Goals**

## California (CPUC Energy Efficiency Strategic Plan)

- 50% of new major renovations to state buildings will be ZNE by 2025.
- 50% of commercial buildings will be retrofit to ZNE by 2030.

## City of San Diego

• Reduce energy consumption at municipal facilities by 15% by 2020 and by 25% by 2035.

## **SDZN3** Project

- Achieve ZNE or near-ZNE at three existing libraries.
- Achieve maximum energy efficiency savings through cost-effective demand-side management technology testing and building monitoring.
- Demonstrate the City's ability to deploy this initiative outside of traditional capital improvement processes.
- Create a replicable blueprint for other municipalities.



# **Project ZNE Definition**

"A Zero-Net-Energy Code Building is one where the net amount of energy produced by on-site renewable energy resources is equal to the value of the energy consumed annually by the building, at the level of a single 'project' seeking development entitlements and building code permits, measured using the Energy Commission's Time Dependent Valuation metric... .... A zero-net-energy code building meets an energy use intensity value designated in the Building Energy Efficiency Standards by building type and climate zone that reflect best practices for highly efficient buildings," (2013 Energy Commission Integrated Energy Policy Report, CEC)

<u>CEC equation</u>: [Value of modeled energy consumed] – [net modeled energy produced] = ≤0

The project is also evaluating ZNE site and ZNE source results.



# Getting to Zero



## Phase 1: Pre-retrofit

- 1. Perform building energy audits.
- Identify & install end-use monitoring equipment needs.
- 3. Collect baseline end-use data.
- 4. Create energy models.
- 5. Perform pre-retrofit behavior analysis.
- Identify, assess & design Energy Conservation Measures (ECMs), including pre-commercial technologies.



## Phase 2: Construction


- 7. Select installation contractors.
- 8. Apply for permits.
- 9. Procure equipment.
- 10. Notify library occupants and patrons.
- 11. Install ECMs.
- 12. Perform Commissioning (Cx) & Retrocommissioning (RCx).
- 13. Integrate new & existing systems into building management system.




## Phase 3: Post-retrofit

- 14. Collect 12 months of measurement and verification data.
- 15. Educate & train facility operators.
- 16. Complete post-retrofit occupant behavior analysis.
- 17. Evaluate project results and benefits.








# Path to ZNE (Energy Conservation Measures)

Energy Conservation Measure	Electricity Savings (kWh/yr.)	Total Energy Savings (kBtu/yr.)	Electricity Savings (\$)	Peak Demand Savings (kW)	Est. Installation Costs* (\$)
Lighting Retrofit	160,662	548,179	21,864	39.1	580,927
Lighting Controls	24,528	83,690	2,908	6.5	150,000
HVAC Controls + Tridium Building Automation	38,813	135,365	7,124	33.3	195,000
Plug Load Optimization: BertBrain Plug Load Manager**	14,002	47,775	1485	4.3	10,000
Building Envelope: Window Film and Weatherization	1,699	6,090	274	0.7	7,000
TOTAL	239,704	821,099	33,655	83.9	942,927

<sup>\*</sup> Does not include design, energy modeling and construction management costs



<sup>\*\*</sup> Pre-commercial technology



# **Next Steps**

- Fall 2019 Winter 2020 - Construction!
- Spring 2020 Spring 2021 - 12 Months Measurement & Verification
- Spring 2021 - Final Report!

Check out project updates and resources at <a href="www.energycenter.org/sdzn3">www.energycenter.org/sdzn3</a>

# Lessons Learned for Future Existing Building ZNE Projects

- Know and stick to your ZNE definition.
- Know your delta to ZNE.
- Conduct pre-retrofit submetered monitoring.
- Isolate energy reductions by end-use to achieve maximum savings.
- · Identify the right energy modeling tool for the project & perform additive modeling.
- Cyber security requirements especially for public projects will affect building automation decisions.
- Lighting upgrades and building controls are cost-effective ECMs for existing buildings but many emerging technologies are still cost-prohibitive.
- <u>Best Practice</u>: Perform 12 months of post-retrofit monitoring (don't just rely on "ZNE design" to call it ZNE).
- Be adaptable and be prepared to learn new things. ©

# Additional Research Value of this Project


- Showcases a public, private and nonprofit partnership.
  - ➤ Tested and implemented integrated project delivery and contracting.
- Retrofits existing buildings with unique building characteristics & approx. 10,000 visitors per month.
- Tests pre-commercial plug load management devices that are integrated into building management systems.
- Provides pre- and post-retrofit behavior surveys.
- Conducts knowledge transfer activities.
- All being done to create a blueprint for local governments!














## DPR NATIONAL NET ZERO PORTFOLIO

## 2016

DPR opened its net-zero energy design Washington, DC office in Reston, Virginia and became DPR's first WELL certified building



Washington, DC

## 2019

DPR opens its net-zero, LEED Platinum building. It is targeted to be the first WELL certified office in Austin



Austin, TX

## 2019

The New Sacramento Office is DPR's first ILFI Petal Certified building with Net Positive Energy. Also targeting LEED Platinum & WELL Certification



Sacramento, CA

Next great thing to be designed/built for a better future in a town near you!

Anytown, USA

GETTING TO ZERO FORUM 2019

DPR SMITHGROUP


## DPR NET ZERO ENERGY RECIPE




- Net-Zero Energy features, clockwise from top left: 1. Rooftop photovoltaics 2. Solatubes 3. Expansive windows 4. Rooftop solar thermal water heating system 5. Solar chimney 6. LED lighting 7. AER-DEC sink / ultra low flush plumbing fixtures walls with live plants 9. Building performance monitoring 10. Big Ass fans 11. Vampire shutoff switch 12. Operable windows and roll-up doors for fresh air and natural light


GETTING TO ZERO FORUM 2019


DPR SMITHGROUP

















## ENERGY EFFICIENCY MEASURES ANALYSIS CONTRIBUTING FEATURES IN REDUCTION Annual Energy Consumption and Production Predictions Thermal labyrinth ventilation system (TLVS) to pré-condition air Energy recovery ventilator (ERV) to further pre-condition air 200.000 **\*\*With Carport PV (Future)** Variable Flow Temperature (VRT) HVAC ■Rooftop PV 150,000 system Ventilation decoupling from VRT system ■Exterior Lighting Lighting power density (LPD) 0.35 w/sf ■DHW 100.000 ■ Cooling No vampire switch: self-sensing with daylight harvesting, local dimming, local occupancy sensors tied into lighting & ■ Heating Fans 50.000 plug load ■Interior Lighting Plug/Misc Loads New R-30 roof Dual-pane low-e glazing with thermally Base Design Final Design (March 2018) (June 2018) broken frames **BRUMMITT ENERGY** Future infrastructure setup for peak ASSOCIATES INC demand shaving when market ready ÐΈR **SMITHGROUP**














## CARBON ESTIMATOR

RESULTS



Volume of wood products used: 70 cubic meters (2,432 cubic feet)



U.S. and Canadian forests grow this much wood in:



Carbon stored in the wood: 55 metric tons of carbon dioxide



Avoided greenhouse gas emissions: 115 metric tons of carbon dioxide



Total potential carbon benefit:



170 metric tons of carbon dioxide





33 cars off the road for a year



Energy to operate 14 homes for a year

\*Source: WoodWorks Wood Products Council









DER SMITHGROUP

# NET ZERO STRATEGIES

		DPR San Francisco	DPR Phoenix	DPR Washington DC	DPR Sacramento
	Rooftop solar tube fixtures (Solatubes)	•	•	•	•
	Rooftop daylight harvesting light wells	•	•		
Daylighting	Daylight and Views Strategy, Utilizing Glass Fronts for all Conference Rooms			•	•
	Window Glass, Minimize Glare, and Radiant Heat from Direct Sunlight			•	•
	White countertop surfaces, and acoustical ceiling clouds to extend daylight further into space			•	
	High efficiency and LED fixtures	•	•	•	•
	Low Energy or Energy Star Equipment			•	•
Energy	Single Extra Wide Monitors ILO Dual Monitors at Workstations			•	•
	WELL Circadian Lighting and Visual Balance				•
GETTING TO ZERO FO	DRUM 2019			DPR SI	MITHGROUP


NET Z	ZERO STRATEGIES			NA <sup>1</sup>	
		DPR San Francisco	DPR Phoenix	DPR Washington DC	DPR Sacramento
_	Energy End-Use Measurement Submeters	•	•	•	•
Energy Consumption Awareness	Building Energy Use Dashboard Display (Lucid Designs)	•	•	•	•
Awareness	Occupant Plug Load Management & Measurement System	•		•	•
	Rooftop Photovoltaic (PV) Solar Array	•	•	•	•
Onsite Renewable	Rooftop Solar Water Heating Array	•		•	
Energy Generation	Shaded Parking Photovoltaic (PV) Solar Array		•		•
	Onsite Battery Backup for Resiliency				•
Design	Extensive energy Modeling			•	•
	3rd Party HVAC/Electrical Consultant			•	•
SETTING TO ZERO FO	RUM 2019			DPR SI	MITHGROU

NET Z	ZERO STRATEGIES				
		DPR San Francisco	DPR Phoenix	DPR Washington DC	DPR Sacramento
	Passive Infra-Red Occupancy Controls	•	•	•	•
	Time Controls and Shut-Offs	•	•	•	•
Building Management	Integrated Building Management System	•	•	•	•
	Non-Occupied Energy Circuit Shut-Off – Phantom Load Management Switch	•	•	•	•
	Dedicated Outdoor Air System w/ Water Source Heat Pump/Heat Recovery Chiller & Fan Powered Terminal Units served by a four pipe system.			•	•
	Utilization of Several Energy Efficient Heating/Cooling Radiant Sails			•	
HVAC	Set Points Established on Dew-point, Not Just Temp.			•	
	Simultaneous Energy Recovery from Hot and Cold Water Loops Design - Collaborative Process			•	
	Thermal Labyrinth – Collaborative Process				•
GETTING TO ZERO FOR	RUM 2019			DPR SI	MITHGROUP

	ZERO STRATEGIES				
		DPR San Francisco	DPR Phoenix	DPR Washington DC	DPR Sacrament
HVAC	Expanded Occupancy Thermal Comfort	•			•
	Enhanced air circulation – High Volume, Low velocity ceiling fans (Big Ass Fans)	•			•
	Passive ventilation	•			•
	Evaporative Cooling – Shower Towers		•		
	Natural Ventilation – Operable Windows and Rooftop Monitors – Solar Chimney		•		•
	Exterior Window Shading / Treatments – Green Screens		•	•	•
	Indoor Landscaping (Biophilia)	•	•	•	•
ETTING TO ZERO I	FORUM 2019			DPR SI	MITHGRO













# **REALIZE**: CalRetro

Mass Deployment Model for ZNC Retrofits of Low-income Multifamily Buildings

> Andy Brooks Direct, West Coast Operations Association for Energy Affordability October, 2019



















# **Current State of Deep Energy Retrofits**

- We can do them, but... they take
  - A lot of TIME
  - A lot of MONEY
  - A lot of EFFORT
  - A lot of PEOPLE
  - A lot of COORDINATION
  - A lot...
  - A lot...
  - A lot...



# **Current State of Deep Energy Retrofits**

LIWP Projects Average Energy Savings: 42%, with some projects achieving ZNE and close to ZNE (80% +)

Typical Project Timeline: 1-2 years from initial outreach to construction completion.

Average Incentive Contribution: \$3500-\$4000/unit

Average Total Project Cost: \$7600/unit



## **Deep Energy Savings LIWP Project Example** 79% Energy Savings 83% Utility Cost Savings PROPERTY INFORMATION MONTHLY ENERGY USE • Located in McFarland, CA; built in 1995 • 52 units, 57,716 sq. ft. ■ Projected Solar PV ■ Natural Gas ■ Electricity • Existing DHW: Unitary gas non-condensing tank - switched to heat pump water heaters Existing HVAC: Unitary gas forced air furnace with A/C - switched to **SCOPE OF WORK**

### **Energy Efficiency** Heat Pump Water Heaters (electrification scope)

- Inverter Drive Heat Pumps (electrification scope)
- Ductwork Aerosealing
- . Attic Air Sealing and Insulation
- New ENERGY STAR Washing Machines and Refrigerators Dual Pane Windows
- Comprehensive LED Upgrade
- Low-Flow Aerators and Showerheads

## Renewable Energy

• 171.2 kW solar PV array, 90% allocated to tenant meters





# **ENERGIESPRONG: A MODEL OF INSPIRATION**

Core offering: A net zero carbon retrofit bundle that is 1) affordable, 2) attractive, 3) ensures energy performance, and 4) can be delivered in less than two weeks











Net-zero energy homes with long performance warranties Refurbishment within a week to 10 days

Financeable through energy cost savings

Attractive and comfortable homes



# FACADE PANELS: A VARIETY OF SOLUTIONS









# FACADE INSTALLATION SITE PRE-WORK











# **RENOLUTION PROJECT**

























# Concepts to Adapt from Energiesprong Model

- Design develop scalable systems, focusing on unitized yet customizable panels
- Building science improve on building science while also embracing Dutch spirit of learning through implementation
- Foster innovation Develop multiple solution types
- **Tenant engagement** set expectations on *total* delivery time and collaborate with tenants during planning phase



# **Project Steps**

## **Technical Solutions**

- Building Characterization/Typology
- Emerging Technology Assessment
- Development of Retrofit Packages
- Prototype/Constructability Testing
- Demonstration Projects (design, install, QA/commissioning, EM&V) of industrialized retrofit packages

## **Market Solutions**

- Market Characterization
- Stakeholder Convening's
- Business Plan
- Energy Plan
- Financing Tools
- Market Scaling
- Aggregated Demand
- Technology Transfer





# Thank You!

Andy Brooks 510-431-1791 abrooks@aea.us.org